



PUT OUR ENERGY TO WORK FOR YOU.

Two International Drive, Suite 200, Portsmouth, NH 03801
 Tel (603) 431-1000 FAX (603) 430-7290
 An Axel Johnson, Inc. Company

MATERIAL SAFETY DATA SHEET

**ETHANOL
 GASOLINE**

(Reformulated ~ Conventional)

Content Last Revised 01/19/2004; 06/05
 5 pages.

SECTION 1 - MATERIAL IDENTIFICATION		24 HOUR EMERGENCY INFORMATION	
PRODUCT / CHEMICAL NAME:	GASOLINE 93 OCTANE PREMIUM 89 OCTANE MID-GRADE 87 OCTANE REGULAR	Sprague:	603-431-1000
		Chemtrec:	800-424-9300
PRODUCT / CHEMICAL SYNONYMS:	UNLEADED GASOLINE REFORMULATED (RFG) GAS CONVENTIONAL GASOLINE	HMIS / NFPA HAZARD RATING	<p>← FIRE REACTIVITY ← OTHER HEALTH</p>
CHEMICAL FAMILY / FORMULA:	ALIPHATIC AND AROMATIC PETROLEUM HYDROCARBONS MIXTURE	4=EXTREME 3=SERIOUS 2=MODERATE 1=SLIGHT 0=MINIMAL	
MATERIAL USE OR OCCURRENCE:	BLENDED MOTOR FUEL		

SECTION 2 - INGREDIENTS						
COMPONENT	%	C.A.S. NO.	OSHA PEL	OSHA STEL	ACGIH TLV	OTHER
Benzene	0 - 2.0	71-43-2	1		10	
Light Petroleum Distillate	0 - <99.9	8006-61-9	300		300	
Cumene	0 - <1	98-82-8	50		50	
Ethyl Benzene	0 - <5	100-41-4	100		100	
Toluene	0 - 30	108-88-3	100 TWA/150STEL		50	
Xylene	0 - 25	1330-20-7	100 TWA/150STEL		100	
Naphthalene	0 - 5	91-20-3	10		10	
Cyclohexane	0 - 9	110-82-7	300		300	
O Hexane (all isomers)	0 - 1	NA	500		500	
1,2,4 Trimethyl Benzene	0 - 5	95-63-6	25		25	
Butane	0 - 9	75-28-5	800 TWA ppm		800 TWA ppm	
Ethyl Alcohol (Ethanol)	0- 10	64-17-5	1000 PPM		N/A	

SECTION 3 - PHYSICAL DATA			
BOILING POINT:	100°-430°F (38° -221°C)	% VOLATILITY BY VOLUME:	100%
VAPOR PRESSURE:	325 - 525 (mmHg @ 20°C)	VAPOR DENSITY (AIR = 1):	<4
SPECIFIC GRAVITY	0.74 @15°C where (H2O = 1):	SOLUBILITY IN WATER:	Slight
EVAPORATION RATE (n-butyl acetate = 1): Rapid and varies			
APPEARANCE & ODOR: Colorless liquid. Gasoline odor.			



MATERIAL SAFETY DATA SHEET

ETHANOL
GASOLINE

(Reformulated ~ Conventional)
Content Last Revised 01/19/2004; 06/05.

5 pages

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: -40°F (- 40°C) (Tag. Closed Cup) AUTOIGNITION TEMP: 536 °F (280°C)

FLAMMABILITY LIMITS IN AIR (% BY VOL.) LEL: 1.5 UEL: 7.6

EXTINGUISHING MEDIUM: Foam, carbon dioxide, dry chemical, and water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Evacuate area. For large spills, fire-fighting foam is the preferred agent and should be applied in sufficient quantities to blanket the gasoline surface. Water spray may be used to flush spill away from exposures, but good judgment should be practiced to prevent spreading of the gasoline into sewers, streams or drinking water supplies. If a leak or spill has not ignited, apply a foam blanket to suppress the release of vapors. If foam is not available, a water spray curtain can be used to disperse vapors and to protect personnel attempting to stop the leak.

UNUSUAL FIRE AND EXPLOSION HAZARDS: EXTREMELY FLAMMABLE. Do not store or pour near sources of ignition. Do not pressurize, cut, heat, weld, or expose to sources of ignition. Vapors are heavier than air and may travel a considerable distance to a source of ignition and flash back. Do not mix or store with strong oxidants. Bond and ground all containers/transfers.

SECTION 5 - HEALTH DATA

Table with 3 columns: Exposure Route, Acute Health Effects, Chronic Health Effects. Rows include Inhalation, Ingestion, Skin Contact, and Eye Contact.

FIRST AID PROCEDURES

INHALATION: Remove from vapor to fresh air. If breathing has stopped give artificial respiration. Maintain airway and blood pressure and administer oxygen if available. Keep affected person warm and at rest. Qualified personnel should perform administration of oxygen. Get medical attention immediately.

INGESTION: Do not induce vomiting or give anything by mouth to an unconscious person. When vomiting occurs, keep persons head lower than heart to prevent pulmonary aspiration. Get medical attention immediately. If less than 1/2 pint (liter) ingested, immediately give 1-2 glasses of water and call a physician. Ingestion in small quantities is not expected to be a problem.

SKIN CONTACT: Wash affected area with soap or mild detergent and large amounts of water until no evidence of

**MATERIAL SAFETY DATA SHEET****ETHANOL
GASOLINE**

(Reformulated ~ Conventional)

Content Last Revised 01/19/2004; 06/05.

5 pages

chemical remains (approximately 15-20 minutes). If irritation develops, seek medical aid. Remove fuel soaked clothing and launder before reuse.

EYE CONTACT: Flush eyes immediately with large amounts of water, occasionally lifting upper and lower lids until no evidence of chemical remains (approximately 15-20 minutes). If irritation develops, seek medical aid.

**TOXICOLOGICAL
DATA**

Gasoline and Refinery Streams: Studies conducted by the American Petroleum Institute examined a reference unleaded gasoline for mutagenic, teratogenic and sensitization potential; no evidence of these hazards was found. However, isolated constituents of gasoline may display these or other potential hazards in laboratory tests. There were no significant adverse effects in three-month subchronic inhalation studies in rats or monkeys, or in a two-year skin cancer study in mice. Studies with laboratory concentrations over a prolonged period of time caused kidney damage and kidney cancer in male rats and liver cancer in female mice. There was no evidence of significant adverse systemic or reproductive effects for light catalytic cracked naphthas and reformed naphthas. Components: Gasoline consists of a complex blend of petroleum/processing derived paraffinic, olefinic, naphthenic and aromatic hydrocarbons which include up to 5% benzene (with 1-2% typical in the U.S.), n-hexane, mixed zylenes, toluene, ethylbenzene and trimethyl benzene. Repeated exposures to low levels of benzene have been reported to result in blood abnormalities including anemia and, in rare cases, leukemia in both animals and humans. Prolonged exposure to n-hexane may result in nervous system damage, including numbness of the extremities and, in extreme cases, paralysis. The adverse effects associated with these components have not been observed in studies with gasoline or the refinery streams from which it is formulated. Generally, human exposures to gasoline vapors are considerably less than those used in the animal toxicity studies. As far as scientists know, low level or infrequent exposures to gasoline vapors are unlikely to be associated with cancer or other serious diseases in humans.

SECTION 6 - REACTIVITY DATA

STABILITY:	Stable under normal temperatures and pressures.
HAZARDOUS POLYMERIZATION:	Hazardous polymerization will not occur.
CONDITIONS TO AVOID:	Avoid build-up of static electricity. May be ignited by heat, sparks, or flame. Vapors may travel to a source of ignition and flash back. Vapor explosion hazard indoors, outdoors, or in sewers.
INCOMPATIBLES:	May explode or react violently when exposed to oxidizing materials. Avoid halogens, strong acids and alkalies.
DECOMPOSITION PRODUCTS:	Carbon monoxide, oxides of nitrogen, and hydrocarbons.

SECTION 7 - SPECIAL PROTECTION

RESPIRATORY PROTECTION:	Use with adequate ventilation. Use approved respiratory protection, for large spills or when conducting work in confined spaces.
VENTILATION:	Use in well ventilated area with local exhaust ventilation. Ventilation required and equipment must be explosion proof. Use away from all ignition sources.
EYE PROTECTION:	If splash with liquid is possible, wear chemical type goggles.
PROTECTIVE GLOVES:	Neoprene, PVC
OTHER PROTECTIVE CLOTHING OR EQUIPMENT:	Employee must wear appropriate impervious clothing and equipment to prevent repeated or prolonged skin contact with this substance.

SECTION 8 - SPECIAL PRECAUTIONS

**MATERIAL SAFETY DATA SHEET****ETHANOL
GASOLINE**

(Reformulated ~ Conventional)

Content Last Revised 01/19/2004; 06/05.

5 pages

SAFE HANDLING:	<ul style="list-style-type: none"> NEVER SIPHON GASOLINE BY MOUTH. GASOLINE SHOULD NOT BE USED AS A SOLVENT OR CLEANING AGENT. USE NON-SPARKING TOOLS AND EXPLOSION-PROOF EQUIPMENT. AVOID CONTACT WITH SKIN. AVOID INHALATION OF VAPORS OR MISTS. USE IN WELL VENTILATED AREA AWAY FROM ALL IGNITION SOURCES. PORTABLE CONTAINERS APPROVED FOR STORING FUEL MUST BE PLACED ON THE GROUND AND THE NOZZLE MUST STAY IN CONTACT WITH THE CONTAINER WHEN FILLING TO PREVENT BUILD-UP AND DISCHARGE OF STATIC ELECTRICITY.
STORAGE:	<ul style="list-style-type: none"> DRUMS AND STORAGE CONTAINERS MUST BE GROUNDED AND BONDED AND EQUIPPED WITH SELF-CLOSING VALVES, PRESSURE VACUUM BUNGS AND FLAME ARRESTERS. STORE AWAY FROM ALL IGNITION SOURCES IN A COOL AREA EQUIPPED WITH AN AUTOMATIC SPRINKLING SYSTEM. OUTSIDE OR DETACHED STORAGE PREFERRED.
SPILL AND LEAK PROCEDURES:	<p>DANGER, EXTREMELY FLAMMABLE LIQUID AND VAPOR! Shut off ignition sources (no smoking, shut off flames or flares in hazard area). Isolate hazard area and restrict entry. Run-off may create a fire and explosion hazard in storm drains and sewer systems. If properly trained, proceed with the following measures:</p> <ol style="list-style-type: none"> For small spills, take up with sand or other absorbent material and place into containers for later disposal; and, For large spills, dike far ahead of spill to prevent entrance into watercourses and/or ground water. Observe local, state, and federal governmental regulations.
WASTE DISPOSAL METHOD	<ol style="list-style-type: none"> Under EPA RCRA (40 CFR 261.21) If this product becomes a waste material intended for disposal, it would be ignitable hazardous waste (waste code number D001). It may also have TCLP benzene concentration greater than 0.5 PPM, and it would be considered a toxic waste (waste code number D018). Refer to latest EPA and State regulations regarding proper disposal.

SECTION 9 - DOT HAZARDOUS MATERIAL INFORMATION

PROPER DOT SHIPPING NAME: GASOLINE; 3; UN 1203, PGII		LABEL: FLAMMABLE LIQUID	REQUIRED PLACARDING: FLAMMABLE / UN 1203
HAZARD CLASS: CLASS 3 (Flammable liquid)	PACKING GROUP (P.G.): II	N.A./U.N. NUMBER: UN 1203 (Note, Emergency Response Guide #128)	RQ: N/A

SECTION 10 - EPA SARA TITLE III INFORMATION

SECTION 311/312 HAZARD CLASSIFICATION:	ACUTE: YES	CHRONIC: YES
	FIRE: YES	PRESSURE: NO
		REACTIVE: NO

SECTION 11 - REMARKS

This product contains no "extremely hazardous substances". The product does contain components that may require reporting under SARA (313) Toxic Release. Please refer to section 2 Ingredients and associated component concentrations.



MATERIAL SAFETY DATA SHEET

**ETHANOL
GASOLINE**

(Reformulated ~ Conventional)

Content Last Revised 01/19/2004; 06/05.

5 pages

SECTION 12 - ADDITIONAL REGULATORY DATA

PRECAUTIONARY LABEL TEXT:

CONTAINS GASOLINE DANGER! FOR INDUSTRIAL USE ONLY!

EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. MAY CAUSE EYE, SKIN, NOSE, THROAT AND LUNG IRRITATION, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS. LOW VISCOSITY MATERIAL-IF SWALLOWED MAY BE ASPIRATED AND CAN CAUSE SERIOUS OR FATAL LUNG DAMAGE.

LONG-TERM EXPOSURE TO GASOLINE VAPOR HAS CAUSED KIDNEY AND LIVER CANCER IN LABORATORY ANIMALS.

Keep away from heat, sparks, and flame. Avoid all personal contact. Avoid prolonged breathing of vapor. Keep container closed. Use with adequate ventilation. Misuse of gasoline may cause serious injury or illness. For use as a motor fuel only. Not to be used as a solvent or skin cleaning agent. Never siphon by mouth.

FIRST AID: If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician immediately. In case of contact, immediately wash skin with soap and plenty of water. Remove contaminated clothing. Call a physician if symptoms occur. Wash clothing before reuse. If swallowed, seek immediate medical attention. Do not induce vomiting. Only induce vomiting at the instruction of a physician. Do not induce vomiting or give any thing by mouth to an unconscious person.

The information contained herein is based on data available at this time and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Since information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, no responsibility is assumed for the results of its use. The person receiving this information shall make his own determination of the suitability of the material for his particular purposes.